


Kawa Deus

Microleather collection

Technical data sheet

| GENERAL | | |
|------------------------------------------------------------------------------------------------------|------------------------------------------------------|----------------------|
| Composition surface | | 100%PU |
| Composition back cloth | | 100%Rayon |
| Roll width | | 137cm |
| Roll length | | 40m |
| Weight | | 377gr/m ² |
| Thickness | | 1.1mm |
| TESTS | METHOD | RESULT / U.M. |
| Colour fastness to light | UNI EN ISO 105 B02 | 7 |
| Flexing endurance Bally Flex | UNI EN ISO 4818-13 + PDP 171 | 100.000 cycles |
| Resistance to blocking | UNI EN ISO BS 3424 | no blocking |
| Hidrolisis resistance (>100.000 cycles, > 10 years) | UNI 4818-29 / 4818-13 | no damage |
| Martindale abrasion | UNI EN ISO 12947-2 | 75.000 rubs |
| Colour fastness to rubbing (dry) | UNI EN ISO 11640 | 5 |
| Colour fastness to rubbing (wet) | UNI EN ISO 11640 | 4-5 |
| Burning behaviour | UNI EN ISO FR 1021 part 1+2 FR BS 5852 source 0+1 | Pass |
| CERTIFICATS | | |
| Chrome free | | |
|  FIRE RETARDANT | | |
| CLEANING INSTRUCTIONS | | |
| Slightly wet towel. Neutral soap. | | |

REMARKS

INTENSIVE CONTRACT AND DOMESTIC USE

Slight color differences between production batches can occur.

The test results only apply to the samples tested.

Buvetex can't be kept liable for inappropriate use of the microleather.

